In the claims:

For the Examiner's convenience, all pending claims are presented below with changes shown. Please cancel claims 4, 11 and 18 without prejudice.

3037406962

1. (Currently Amended) A method comprising:

a processor at a first node determining one or more communication protocols via which a second node is capable of communicating with the first node based upon one or more parameters received from the second node during an initialization of communication between the first node and the second node, the one or more parameters specifying the one or more communication protocols;

the processor selecting first drivers to implement an Ethernet protocol if the one or more parameters specify the first communication protocol; and

the processor selecting second drivers to implement an Asynchronous Transfer Mode protocol if the one or more parameters specifies the second protocol; and

in response to the selecting, invoking a plug and play (PnP) protocol manager to initiate loading of the one or more drivers into memory.

2-5. (Cancelled)

6. (Previously Presented) The method of claim 1, wherein: the first node comprises at least one modern driver; and the determining is performed by the at least one modern driver.

Docket No. 42P16159 Application No. 10/646,958

P.6/13

7. (Previously Presented) The method of claim 1, wherein:

the initialization of the communication comprises a negotiation between the first node and the second node; and in response to a request from the first node, the second node transmits during the negotiation the one or more parameters to the first node.

8. (Currently Amended) An apparatus comprising:

a first node, including:

a memory device to store first drivers and second drivers; and

a processor at a first node to determine one or more communication protocols via which a second node is capable of communicating with the first node based upon one or more parameters received by the first node from the second node during an initialization of communication between the first node and the second node, the one or more parameters specifying the one or more-communication protocols, to select the first drivers to implement an Ethernet protocol if the one or more parameters specifies the first communication protocol and to select the second drivers to implement an Asynchronous Transfer Mode protocol if the one or more parameters specifies the second protocol and to invoke a plug and play (PnP) protocol manager to initiate loading of the one or more drivers into memory.

the processor selecting first drivers to implement protocol if the one or more parameters specify the first communication protocol;

9-12. (Cancelled)

- 13. (Previously Presented) The apparatus of claim 8, wherein:

 the processor is capable of executing at least one modern driver; and

 execution of the at least one modern driver by the processor results in the processor

 being capable of determining the one or more-communication protocols.
- 14. (Previously Presented) The apparatus of claim 8, wherein:

 the initialization of the communication comprises a negotiation between the first node and the second node; and in response at least in part to a request from the first node, the second node transmits during the negotiation the one or more parameters to the first node.
- 15. (Currently Amended) An article comprising: a storage computer-readable medium having stored thereon instructions that when executed by a machine computer result in the following:

at a first node determining one or more communication protocols via which a second node is capable of communicating with the first node based upon one or more parameters received from the second node during an initialization of communication between the first node and the second node, the one or more parameters specifying the one or more communication protocols;

the processor selecting first drivers to implement an Ethernet protocol if the one or more parameters specify the first communication protocol; and

Docket No. 42P16159 Application No. 10/646,958 the processor selecting second drivers to implement an Asynchronous Transfer Mode protocol if the one or more parameters specifies the second protocol; and

in response to the selecting, invoking a plug and play (PnP) protocol manager to initiate loading of the one or more drivers into memory.

16-19. (Cancelled)

- 19. (Canceled)
- 20. (Previously Presented) The article of claim 15, wherein:

 the first node comprises at least one modem driver; and

 the determining of the at least one communication protocol is performed by the at
 least one modem driver.
- 21. (Previously Presented) The article of claim 15, wherein:

the initialization of the communication comprises a negotiation between the first node and the second node; and in response to a request from the first node, the second node transmits during the negotiation the one or more parameters to the first node.

22. (Previously Presented) A system comprising:

a first node comprising:

circuitry that includes a circuit card; and

a circuit board that includes a circuit card slot that is capable of coupling the circuit card to the circuit board; and

a second node;

which the second node is capable of communicating with the first node based upon one or more parameters received by the circuit card from the second node during an initialization of communication between the first node and the second node, one or more parameters specifying the one or more communication protocols, to select first drivers to implement an Ethernet protocol if the one or more parameters specifies the first communication protocol and to select second drivers to implement an Asynchronous Transfer Mode protocol if the one or more parameters specifies the second protocol.

23. (Original) The system of claim 22, wherein:

the circuit board comprises a bus and a host processor coupled to the bus; and when the circuit card is coupled to the slot, the circuitry is coupled to the bus.

- 24. (Original) The system of claim 23, wherein:
 the circuit card comprises a digital subscriber line (DSL) modem.
- 25. (Original) The system of claim 24, wherein:

Docket No. 42P16159 Application No. 10/646,958

P.10/13

a central office (CO) comprises the second node; and customer premises equipment (CPE) comprises the modem.